Waste-exit

SP 005 708-SC

with integrated screw compactor.

Technical data:

Integrated fans:	TRL40	TRL75	TRL200
	4,0Kw	5,5Kw	7,5Kw
	2.000 m ³	2.400 m ³	3.500 m ³
	4.500pa	5.600pa	7.500pa
Free filter area:	Flat: 0,8 m		el: 2,1m²
Air capacity:	2.400 m³/ł		0 m3/h
Filter types:	2 pcs. Woven polyester bags 2 pcs. Panel filter 930*460*47mm		

System control box.



The control unit is running on a PLC and operated from the screen on the front of the control box.

All parameter and timer settings changeable

Remote connections: Start/Stop Alarm Fan control

The perfect solution for collecting and compacting up to 100 kg waste and lint per day.

Works with continuous vacuum.

Usability:

The compactor can be used in off-cut waste from sewing machines and for paper and PVC.

Function of the compactor:

The screw is rotating continuously and when waste drops down, it's compressed into the bag. The compression can be from 5 kg to 40kg. The bags can be made into the size of demand.

www.waste-exit.dk Phone: +45 9713 1899 e-mail: sales@ibjuncker.dk Finlandsvej 4, DK 7480 Vildbjerg

Ib Juncker engineering Aps.